

PRODUCT: PVC MATTING STUDED (BOLLE) 1 mm thickness



| | | | |
|------------------------------------|---|-------------|---------------------------------|
| COMPOSITION: | PVC , plasticizers, fillers and color masterbatch | | |
| PRODUCTION PROCESS | CALANDERING AND LAMINATION OF WEAR LAYER, DESING AND BACKING LAYER | | |
| DIMENTIONS (at 25°C) | WEIGHT | 1500gr/m2 | +/-10% |
| | WIDTH | 200 and 100 | +2%/-0% cm |
| | LENGHT | 25m | +2%/-0% |
| | THICKNESS | 1mm | +/-5% OTHER THICKNESS AVAILABLE |
| | WEAR LAYER THICKNESS | 0,12mm | BACKING THICKNESS 0,88mm |
| | DIMENSIONAL VARIANCE CAUSED BY TEMPERATURE VARIANCE +/-5% /10°C variation | | |
| BACKING | PLAIN | | |
| COLOR | BLACK, GREY, ANTHRACITE, BLUE, RED | | |
| HARDNESS | 80 SHORE A +/-10% | | |
| TENSILE STRENGTH | 65 Kg/cm2 +/-10% | | |
| DENSITY | 1,5 Kg/cm3 +/-10% | | |
| RESIDUAL INDENTATION | 0,1mm max | | |
| COLOR FASTNESS | >5 | | |
| ACOUSTIC ISOLATION | >2db | | |
| TEAR STRENGTH | 10 Kg/cm2 +/-10% | | |
| RANGE OF TEMPERATURE OF USE | 10°C/50°C | | |
| CHEMICAL | NOT RESISTANT TO OIL, GREASE, ACIDS, ALKALIS, HYDROCARBONS AND SOLVENTS AVAILABLE OTHER QUALITIES WITH CHEMICAL RESISTANCE CLEAN IMMEDIATELY THE SURFACE IF IN CONTACT WITH CHEMICALS | | |
| FIRE RESISTANCE | CERTIFICATE Bfl S1 | | |
| PACKING | IN WOOD PALLETS SINGLE PACKAGING IN PP SHEET BLACK COLOR LABEL STICKED ON EACH ROLL INNER PIPE 10 CM DIAMETER WITH 2 SIDES PVC PLUGS PACKED WITH DESIGN FACING TO OUTSIDE | | |
| MADE IN | INDIA | | |
| HS CODE | | | |
| ADVANTAGE | ACOUSTIC ISOLATION USE ON LOW TRAFFIC AREAS LOW COST AND LOW MAINTENANCE DECORATIVE, ATTRACTIVE AND MODERN EASY INSTALLATION | | |
| MAINTENANCE | CLEAN WITH WATER AND NEUTRAL PH CLEANING SOLUTION FOR FLOORING DILUTED | | |
| INSTALLATION | ADHESIVE: RUBBER BASED ADHESIVE FOR MATTING ENSURE SUBSTRATE IS SMOOTH, CLEAN, DRY AND STRUCTURALLY SOUND | | |
| UPDATED | 10.4.2014 | | |